



Flaw Detection

FD100 PA 16:64

Metal and composite flaw detection using ultrasound



Compatibility

Proceq offers the possibility to order customized accessories such as probes, wedges and calibration blocks so that our solution is tailor-made to your need.



Ease of use

Plug-and-play compatibility with a wheel probe for fast and efficient corrosion mapping or large composites inspection.



Productivity

C-scans can be displayed in amplitude or depth.
With merged C-scans, data is displayed for all inspection passes in the same view.



Tech Specs

| Display | TFT 8.4" |
|-------------------|--|
| File Size | Up to 3 GB |
| Report Generation | Customisable pdf report, PNG screen capture, CSV file output option |
| Encoder | 1 or 2 axis (quadrature input) |
| Languages | English, German, French, Spanish, Russian, Chinese, Hungarian, Italian, Portuguese, and Japanese |



Instrument Tech Specs

| Configuration | 2 UT & 1 I-PEX Channels | | |
|-----------------------|--|--|--|
| Transducer Socket | Lemo1 - BCD I-PEX | | |
| Pulse Voltage | 25 to 75 V (in 5 V steps) | | |
| PRF | 1 to 5000 Hz | | |
| Gain Range | PA: 76 dB (0.1 dB steps) | | |
| Bandwidth | PA: 200 KHz to 14 MHz UT 200 KHz to 22 MHz | | |
| Display | TFT 8.4" | | |
| Signal Enhancement | Digital filters, smoothing, contouring, rejection, averaging | | |
| Architecture | 16 active, multiplexed over 64 channels | | |
| Digitizing Frequency | 65 MHz | | |
| Focal Laws | 128 | | |
| Maximum A Scan Length | 4096 | | |
| Supported Scans | A, B, C, L, S-Scan, Merged, true Top & End | | |
| Number of Scans | 1 (with up to 3 extracted A scans) | | |
| Number of Layouts | 35 | | |
| Measurements | Path length, depth, surface distance, DAC, AWS, DGS, TGS | | |
| File Size | Up to 3 GB | | |
| Report Generation | Customisable pdf report, PNG screen capture, CSV file output option | | |
| Encoder | 1 or 2 axis (quadrature input) | | |
| Languages | English, German, French, Spanish, Russian, Chinese, Hungarian, Italian, Portuguese, and Japanese | | |
| Battery Life | 6 Hrs | | |
| IP rating | IP66 | | |
| | | | |

| Standards & Guidelines | Description |
|------------------------|-------------|
| ΓΟCT 14782 | |
| ΓΟCT 55724 | |
| EN 12668-1 | |
| ISO 18563-1 | |





Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors. www.screeningeagle.com

Request a quote



