





## Flaw Detection

# **FD100 UT**

Ultrasound Inspection for different type of materials, metal and not metal, such as composite or plastic



## **Upgrade-ready**

The Proceq Flaw Detector 100 can be upgraded with the Ultrasonic Time of Flight Diffraction (TOFD) and Phased Array (PA) modes anytime and anywhere, even on-site.



#### **Precision**

It offers outstanding, powerful hardware, a true square wave pulser, 200MHz digitizing frequency, broad system bandwidth from 200 kHz to 20 MHz, and twin axis encoding to offer users an extremely comprehensive measurement solution.



#### Interactive

With a built-in 3D beamtool showing the part, weld, wedge, probe, scan coverage, and a real-time interactive ray-tracer which plots the beam path and indication location directly in the part. This powerfully helps assess and communicate the indication location easily.





Configuration	2 UT Channels
Transducer Socket	Lemo 1 or BNC
Pulse Voltage	100 to 450 V (square pulse)
PRF	1000 to 1500 Hz
Gain Range	100 dB (0.1 dB steps)
Bandwidth	0.2 - 22 MHz
Display	TFT 8.4"
Signal Enhancement	Digital filters, smoothing, contouring, rejection, averaging
Architecture	2 channels, true 200 MHz sampling rate
Digitizing Frequency	50 MHz, 100 MHz, 200 MHz
Supported Scans	A, B, C, Top and End
Number of Scans	Up to 2
Number of Scans Number of Layouts	Up to 2 18
	•
Number of Layouts	18 Path length, depth, surface distance, DAC,
Number of Layouts  Measurements	18 Path length, depth, surface distance, DAC, AWS, DGS
Number of Layouts  Measurements  File Size	18 Path length, depth, surface distance, DAC, AWS, DGS Up to 3 GB Customisable pdf report, PNG screen capture,
Number of Layouts  Measurements  File Size  Report Generation	Path length, depth, surface distance, DAC, AWS, DGS Up to 3 GB Customisable pdf report, PNG screen capture, CSV file output option
Number of Layouts  Measurements  File Size  Report Generation  Encoder	Path length, depth, surface distance, DAC, AWS, DGS Up to 3 GB Customisable pdf report, PNG screen capture, CSV file output option 1 or 2 axis (quadrature input) English, German, French, Spanish, Russian, Chinese, Hungarian, Italian, Portuguese, and

Standards & Guidelines	Description
ΓΟCT 14782	
ΓΟCT 55724	
EN 12668-1	





Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors. www.screeningeagle.com

Request a quote



