



Zehntner Marking Retroreflection

ZRM 6014 RL-Qd

Day and night visibility measurement of road markings with retroreflectometry



Versatility

Fold-away telescopic handle and wheels standard allowing for superior portability. Gather data for night and day visibility effectively, anytime and on any road surface.



Accuracy

Intelligent electronics paired with Swiss Made optics deliver a new benchmark of measurement, accuracy, and ultrafast retroreflection measurement (RL and Qd) in about 2 seconds



Productivity

Refine your measurements with precise geolocation and high-res images. The user-friendly software makes comprehensive reports quickly and with ease.











Instrument Tech Specs

| Technology | High-resolution Camera Optional compass and level-meter GPS, internal printers |
|-----------------------|--|
| Display | Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution |
| Memory | 1 GB internal flash memory |
| Measurement Modes | R _L dry (night visibility) R _L wet (night visibility) Qd (day visibility) °C/°F (ambient temperature) rH % (relative humidity) |
| Measuring Area | (WxL): 52 mm x 218 mm (2.05" x 8.58") |
| Measuring Range | R _L : 0 - 4'000 mcd·m ⁻² ·lx ⁻¹ Qd: 0 - 400 mcd·m ⁻² ·lx ⁻¹ |
| Measuring Accuracy | Repeatability ± 2 % |
| Observation Angle | EN 1436 & ASTM E2302: 2.29° ASTM E1710: 1.05° |
| Illumination Angle | R _L : EN 1436: 1.24° R _L : ASTM E1710: 88.76° Qd: diffuse |
| Reporting software | Includes mapping and data analysis software MappingTools |
| Weight | 7.6 kg (16.76 lbs) |
| Operating Temperature | -10°C to +50°C (14°F to 122°F) |

| Standards & Guidelines | Description |
|-----------------------------|---|
| ASTM E1710-18 | Standard Test Method for Measurement of Retroreflective Pavement Marking Materials with CEN-Prescribed Geometry Using a Portable Retroreflectometer |
| ASTM E2177 | Standard Test Method for Measuring the Coefficient of Retroreflected Luminance (RL) of Pavement Markings using the Bucket Method in a Condition of Wet Recovery |
| ASTM E2302 | |
| CIE 54.2 | |
| DB 51 T2429 | |
| EN 13197 | |
| EN 1436 | |
| GB/T 16311 (United Kingdom) | |
| GB/T 21383 (United Kingdom) | |
| JT/T 690 | |





Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors. www.screeningeagle.com

Request a quote



