




Zehntner Marking Retroreflector **ZRM 6010 RL**

Night visibility. Continuous wetting and rain conditions.



Versatility

Gather data for night visibility effectively under any weather conditions, at day or night, on any road surface



Accuracy

Telescopic handle for easy field and laboratory operation —the result is a new benchmark of measurement accuracy and robustness under any conditions in the field



Productivity

Enrich your measurements with precise geolocation and high resolution images. The user friendly analysis software makes comprehensive reports possible quickly and with ease



Software / Workspace App

Display	Touchscreen 5.7" color TFT (LCD), LED backlight, VGA resolution
Memory	1 GB internal flash memory



Processing Unit / Sensor

Display	Touchscreen 5.7" color TFT (LCD), LED backlight, VGA resolution
Memory	1 GB internal flash memory
Measurement Modes	R _L dry (night visibility) R _L wet (night visibility) R _L continuous wetting (night visibility) °C/°F (ambient temperature) rH % (relative humidity)
Measuring Area	(WxL): 52mm x 489mm (2.05" x 19.25")
Measuring Range	R _L : 0 - 4'000 mcd•m ⁻² •lx ⁻¹
Measuring Accuracy	Repeatability ± 2 %
Observation Angle	EN 1436: 2.29° ASTM E1710: 1.05°
Illumination Angle	EN 1436: 1.24° ASTM E1710: 88.76°
Weight	6.4kg (14.11 lbs)
Operating Temperature	0°C to +50°C (32°F to 122°F), non condensing

SWISS  MADE

Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.
www.screeningeagle.com

Request a quote

