



Automatic film applicators

## ZAA2600.SW

Linear abrasion tester for wet abrasion, scrub resistance, washability and crocking tests



### User experience

The easy-to-use touchscreen with multi-language menu guidance saves you time in the laboratory and streamlines the entire testing process



### Efficiency

Storage of various profile settings such as stroke length and number of cycles



### Reliability

Modular and flexible design allow easy change of application



## Software / Workspace App

### Display

Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution



## Processing Unit / Sensor

### Material housing

Anodised aluminium

### Weight

≈20 kg (≈44.1 lbs)

### Display

Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution

### Test Weight

Up to 4.5 kg (9.92 lbs) can be applied

### Stroke Length

1 - 320 mm (0.04 - 12.60"), stepless adjustability

### Stroke Speed

1 - 600 mm/s (0.04 - 23.62"/s) and up to 100 double strokes per minute respectively

### Power supply

100 V - 240 V, 50 Hz - 60 Hz

### Resolution

Resolution: 1 mm/s (0.04"/s)

SWISS  MADE

Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.

[www.screeningeagle.com](http://www.screeningeagle.com)

Request a quote

