



Automatic film applicators

## ZAA2600.HA

Automatic Film Applicator for use with Heatable Plates




### User experience

Multi-language menu guidance on the touch screen with storage of various application profile settings such as application length and drawing speed.



### Reliability

Reproducible, operator-independent results allow for storage of various application profile settings such as application length and drawing speed.



### Versatility

Thanks to its modular construction and compact design, it can be equipped with different kits for applications like scrub resistance, washability, crocking, and scratch resistance tests.



**Instrument**  
**Tech Specs**

Display	Touchscreen 5.7" colour TFT (LCD), LED backlight, VGA resolution
Application length	Application length: up to ≈ 400 mm (≈ 15.75")
Application width	Application width: up to 300 mm (11.81")
Weight	2600.HA: ≈ 24 kg (≈ 52.9 lbs) glass plate only: 6.4 kg (14.1 lbs)
Battery	Power supply: 100 V - 240 V, 50 Hz - 60 Hz
Operating Temperature	Plates: heatable up to 150°C (302°F)
Temperature range	Ambient conditions for operation: 5°C to +45°C (41 °F to 113 °F)
Relative humidity	20% to 80%, no condensation
Drawing speed	1 - 500 mm/s (0.04 - 19.69"/s)
Resolution	Resolution: 1 mm/s (0.04"/s)

Standards & Guidelines	Description
ASTM D1640 (Depending on accessory)	
ASTM D4748-10	
ASTM D6279	
ASTM D823 (Depending on accessory)	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

Request a quote



Machine translated & automatically generated (English version prevails): 03.04.2025  
 Copyright © 2023 Screening Eagle Technologies AG or its affiliates. All rights reserved.

