



## Pundit Ultrasonic Pundit 250 Array

Deep scanning of concrete and fiber-reinforced concrete




### Modularity

Full modular system allows you to increase the number of channels by simply attaching additional probes.



### Realtime B-scan

The unique real-time B-scan and panorama views provide high-resolution imaging directly on-site.



### Versatility

The same instrument can be used with classic pulse velocity transducers.



**Instrument**  
**Tech Specs**

Bandwidth	35 kHz to 40 kHz
Technology	Multi-channel ultrasonic pulse echo
Measuring Resolution	0.1 us
Pulse Voltage	±150 V (UPE)
Receiver Gain	1 to 10'000x (0 to 80 dB)
Nominal Transducer Frequency	40 kHz
Pulse Shape	Square wave
Pulse Delay	8 ms – 200 ms
Number of Channels	8 (with upgrade option to 16)
PC Software	PL-Link for analysis and export of data to third party applications
Display	7" color rugged touchscreen unit (800 x 480 pixels) with a dual-core processor
Memory	Internal 8 GB flash memory
Connections	USB host/device and Ethernet
Measurement Modes	Real time B-Scan Panorama B-Scan
Measuring Range	Ca. 1m depending on concrete quality
Special Features	Instrument Firmware: Raw data export Settings directly accessible on measuring screen
Transducers	Dry-contact Pundit Array transducer with auxiliary LCD display and control buttons on handles

## Our Accessories

Image	PartNumber	Description
	Pundit 250 Array	Upgrade to 16 channel: Pundit Array Transducer (327 30 100), Pundit Array Transducer, Extension Kit (376 30 377), and Dual Handle Kit (327 30 370)...

Standards & Guidelines	Description
ACI 228.2R-13	
DGZfP Guideline MC 1	
RI-ZFP-TU	
ZTV-ING Teil 5 Tunnelbau	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.  
[www.screeningeagle.com](http://www.screeningeagle.com)

[Request a quote](#)



