
proceq
A Screening Eagle Company



Schmidt Rebound Hammers

Schmidt OS-120

Pendulum hammer for testing on softer material such as lightweight concrete, gypsum boards, fresh concrete and mortar used for brickwork joints

Resolution & depth


Only rebound hammer that provides a test result at compressive strengths below 5 Mpa.

Versatility

Large, half-circular scale with high resolution.

User Experience

Two models for fresh concrete and mortar applications.













Instrument
Tech Specs

Impact Energy	0.833 Nm
Compressive Strength Range	1 to 5 N/mm2 (145 to 725 psi)
Display	Mechanical display

Standards & Guidelines	Description
Austrian Guideline for tunnel lining, published December 2012. Austrian Construction Association	
TNO Report BI -88-009/61.8.2060-VOE from IBBC Delft Netherlands (Mortar joint testing)	

SWISS MADE

Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.
www.screeningeagle.com

Request a quote

SCREENING EAGLE | proceq

Machine translated & automatically generated (English version prevails): 21.07.2026
Copyright © 2023 Screening Eagle Technologies AG or its affiliates. All rights reserved.