



Zehntner Marking Retroreflection

ZRM 6010 RL

Night visibility. Continuous wetting and rain conditions.



Versatility

Gather data for night visibility effectively under any weather conditions, at day or night, on any road surface



Accuracy

Telescopic handle for easy field and laboratory operation —the result is a new benchmark of measurement accuracy and robustness under any conditions in the field



Productivity

Enrich your measurements with precise geolocation and high resolution images. The user friendly analysis software makes comprehensive reports possible quickly and with ease













Instrument Tech Specs

| Technology | GPS, internal printer | | |
|---------------------|---|--|--|
| Display | Touchscreen 5.7" color TFT (LCD), LED backlight, VGA resolution | | |
| Memory | 1 GB internal flash memory | | |
| Measurement Modes | $\begin{split} R_L & \text{ dry (night visibility)} \\ R_L & \text{ wet (night visibility)} \\ R_L & \text{ continuous wetting (night visibility)} \\ ^\circ C'^F & \text{ (ambient temperature)} \\ \text{rH } \% & \text{ (relative humidity)} \end{split}$ | | |
| Measuring Area | (WxL): 52mm x 489mm (2.05" x 19.25") | | |
| Measuring Range | R _L : 0 - 4'000 mcd•m ⁻² •lx ⁻¹ | | |
| Measuring Accuracy | | | |
| moddaining Accuracy | Repeatability ± 2 % | | |
| Observation Angle | Repeatability ± 2 % EN 1436: 2.29° ASTM E1710: 1.05° | | |
| | EN 1436: 2.29° | | |
| Observation Angle | EN 1436: 2.29° ASTM E1710: 1.05° EN 1436: 1.24° | | |
| Observation Angle | EN 1436: 2.29° ASTM E1710: 1.05° EN 1436: 1.24° ASTM E1710: 88.76° Includes mapping and data analysis software | | |

| Standards & Guidelines | Description |
|------------------------------|--|
| ASTM E1710-18 | Standard Test Method for Measurement of Retroreflective Pavement Marking Materials with CEN-Prescribed Geometry Using a Portable Retroreflectometer |
| ASTM E2177 | Standard Test Method for Measuring the Coefficient of Retroreflected Luminance (RL) of Pavement Markings using the Bucket Method in a Condition of Wet Recovery |
| ASTM E2832-12(2017) | Standard Test Method for Measuring the Coefficient of Retroreflected Luminance of Pavement Markings in a Standard Condition of Continuous Wetting (RL-2) |
| CIE 54.2 | |
| DB 51 T2429 | |
| EN 13197 | |
| EN 1436 | |
| GB/T 16311 (United Kingdom) | |
| GB/T 21383 (United Kingdom) | |
| JT/T 690 | |





Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors. www.screeningeagle.com





