

Pundit Ultrasonic

Pundit 200

Concrete properties analysis using ultrasound pulse velocity



Diverse

In addition to the standard pulse velocity measurement, various measurement modes including surface velocity measurement, Line Scan, Area Scan, Data Logging, compressive strength correlations, SONREB and Emodulus measurement.



Automation

The area scan grid can be freely defined by the user and the colour coded results can display either pulse velocity or depth variations on the structure to quickly identify areas of concern.



Versatility

Provides the unique capability to use the same display device for both classical pulse velocity testing and pulse echo testing.







Instrument Tech Specs

Bandwidth	20 to 500 kHz		
Technology	Ultrasonic pulse velocity		
Measuring Resolution	0.1 us		
Pulse Voltage	±100 to ±450 V (UPV)		
Receiver Gain	1 to 10'000x (0 to 80 dB)		
Nominal Transducer Frequency	24 – 500 kHz		
Pulse Shape	Square Wave		
Pulse Delay	-		
Number of Channels	1		
PC Software	PL-Link for analysis and export data to third party applications		
Display	$7^{\prime\prime}$ color rugged touchscreen unit (800 x 480 pixels) with a dual-core processor		
Memory	>Internal 8 GB flash memory		
Connections	USB host/device and Ethernet		
Measurement Modes	Pulse velocity Surface velocity Data logging E-modulus Compressive strength correlation Crack depth Line Scan Area Scan		
Measuring Range	Up to 15 m depending on concrete quality		
Special Features	Zoom and scroll for precise A-Scan inspection On board storage and review of waveforms Settings directly accessible on measuring screen Dual cursor for manual A-Scan evaluation Separate cursor to measure signal amplitude Automatic and manual triggering and useradjustable trigger threshold A-Scan update rate up to 25 Hz		
Transducers	Available Proceq transducers: 54 kHz, 150 kHz, 250 kHz, 54 kHz exponential, 500 kHz and 40 kHz shear wave dry point contact. Connect third party transducers with a standard BNC connector up to 500 kHz.		

Our Accessories

Image	PartNumber	Description
6 4	32540176	Designed for use on rough or curved surfaces with or without coupling gel.
pr to con.	32701033	Replacement battery for the display unit. Can be charged externally with the batter charger.
•	32701053	Charge an empty battery to 80 % in 3h. Full charge in 5.5 h.
- Accordance Acco	32540210	Designed for use on rough or curved surfaces with or without coupling gel.
	Pundit 200	

Standards & Guidelines	Description
ГОСТ 17624	
ASTM C 597-02	
CECS 21	
EN 12504-4	
IS 13311	
ISO 1920-7:2004	





Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swissmanufactured sensors.

www.screeningeagle.com

Request a quote



