




Zehntner Marking Retroreflection **ZRM 6013+ RL-Qd**

Professional retroreflectometer for day and night visibility



Efficiency

Ultrafast retroreflectometer measurement (RL and Qd) in about 2 seconds for all types of road markings



Versatility

Use in dry or wet conditions at any time of day or night on the road or in the laboratory



User Experience

5.7" high resolution colour touchscreen with excellent visibility under all light conditions



Instrument Tech Specs

Display	Touchscreen 5.7" color TFT (LCD), LED backlight, VGA resolution
Memory	1 GB internal flash memory
Measurement Modes	R _L dry (night visibility) R _L wet (night visibility) Qd (day visibility) °C/°F (ambient temperature) rH % (relative humidity)
Measuring Area	(WxL) 52mm x 218mm (2.05" x 8.58")
Measuring Range	R _L : 0 - 4'000 mcd·m ⁻² ·lx ⁻¹ Qd: 0 - 400 mcd·m ⁻² ·lx ⁻¹
Measuring Accuracy	Repeatability ± 2 %
Observation Angle	EN 1436 & ASTM E2302: 2.29° ASTM E1710: 1.05°
Illumination Angle	R _L : EN 1436: 1.24° R _L : ASTM E1710: 88.76° Qd: diffuse
Weight	6.8kg (14.99 lbs)
Operating Temperature	-10°C to +50°C (14°F to 122°F), non condensing

Standards & Guidelines	Description
ASTM E1710-18	Standard Test Method for Measurement of Retroreflective Pavement Marking Materials with CEN- Prescribed Geometry Using a Portable Retroreflectometer
ASTM E2177	Standard Test Method for Measuring the Coefficient of Retroreflected Luminance (RL) of Pavement Markings using the Bucket Method in a Condition of Wet Recovery
ASTM E2302	
CIE 54.2	
EN 13197	
EN 1436	

SWISS  MADE



Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.

www.screeningeagle.com

Request a quote



